

Horizontal Openwell Submersible Monobloc Pumpsets. At 2880 RPM with 415 Volts, Three Phase, AC, 50 Hz Supply

Sl. No.	Pump Model	HP/KW	Pipe Size in mm	Total Head in Metres	6	8	10	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46	48	50		
1	OVM 3	3.0/2.2	50	Discharge in LPM	690	672	648	594	540	516	492	450	366	336	252	168													
2	OVM 12	3.0/2.2	50				780	725	675	620	600	510	480	380	280	100													
3	OVM 30	3.0/2.2	65			1140	1032	960	906	810	720	552																	
4	OVM 31	3.0/2.2	75			1248	1164	1086	882	732	534																		
5	OVM 4	5.0/3.7	50			900	882	858	834	798	762	714	666	612	546	486	420	348	264										
6	OVM 14	5.0/3.7	50						1020	970	910	890	875	850	800	710	610	480											
7	OVM 20	5.0/3.7	65			1290	1194	1140	1086	1032	948	882	798	696	552	528	492	402											
8	OVM 20HD	5.0/3.7	65			*	1280	1200	1100	1080	960	890	800	670	560														
9	OVM 5	5.0/3.7	75			1608	1488	1344	1236	1128	1014	876	732	486															
10	OVM 38	6.5/4.8	50			*	1002	984	960	930	870	834	798	756	714	678	624	558	480	396	270								
11	OVM 39	6.5/4.8	65			1542	1464	1404	1368	1290	1224	1158	1080	990	900	804	690	540											
12	OVM 6	7.5/5.5	50			*	*	*	*	*	978	960	942	912	876	840	810	762	708	636	594	522	444	366					
13	OVM 22	7.5/5.5	65			*	*	1404	1344	1278	1200	1116	1032	996	954	870	768												
14	OVM 23	7.5/5.5	75			*	*	*	1878	1788	1656	1488	1362	1170	900														
15	OVM 9	10.0/7.5	50			*	*	*	*	*	*	*	*	*	*	*	1194	1170	1134	1104	1050	1014	960	888	828	744	654	522	
16	OVM 10	10.0/7.5	65			*	*	*	*	1488	1476	1458	1440	1434	1302	1266	1206	1140	1062	972	882	774	660	492	240				
17	OVM 25	10.0/7.5	75			*	*	*	2046	1944	1836	1710	1596	1458	1326	1152	984												
18	OVM 50	15.0/11.1	65			*	954	940	925	915	900	890	880	875	865	850	840	830	820	810	800	790	780	760	745	720	710	600	