

Vertical Openwell Submersible Pumpsets. At 2880 RPM with 415 Volts, Three Phase, AC, 50 Hz Supply

Sl. No.	Pump Model	HP/KW	No. Of Stages	Pipe Size in mm	Discharge in LPM	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000		
1	TCM 325	3.0/2.2	2	65	Total Head in Mtrs.				29	27	25	23	20	18	14	11	8							
2	TCM 335	3.0/2.2	3	65		35	33	31	28	26	22	20	16	12	8									
3	TCM 535	5.0/3.7	2	65					34	33	32	31	30	29	27	25	23	21	18	16	14	8		
4	TCM 545	5.0/3.7	3	65		46	44	42	40	38	34	30	26	22	18	11	8							
5	TCM 750	7.5/5.5	3	65			50	49	48	47	45	44	42	40	38	36	33	30	27	23	20	12		
6	TCM 760	7.5/5.5	4	65		58	54	50	45	42	38	34	30	24	10									
7	TCM 1070	10.0/7.5	4	65			63	62	60	58	56	54	51	49	46	43	40	35	30					

TCM Series. At 2880 RPM with 415 Volts, Three Phase, AC, 50 Hz Supply

Sl. No.	Pump Model	HP/KW	Pipe Size in mm	No of Stages	Total Head in Metres	10	20	30	40	50	60	70	80	90	100
1	TCM 340	3.0/2.2	65	2	Discharge in LPM	455	370	280	140						
2	TCM 555	5.0/3.7	65	3		525	480	430	390	270					
3	TCM 775	7.5/5.5	65	4		575	540	500	440	390	320	240			
4	TCM 10110	10/7.5	65	6		580	545	515	480	440	390	345	290	230	115
5	TCM 1080	12.5/9.3	65	5		1050	990	935	860	760	645	460	170		

Horizontal Openwell Two Stage Submersible Pumpsets. At 2880 RPM with 415 Volts, Three Phase, AC, 50 Hz Supply

Sl. No.	Pump Model	HP/KW	Pipe Size in mm	Total Head in Metres	12	14	16	18	20	22	24	26	28	30	32	34	36	38	40	42	44	46
1	MRF 4	5.0/3.7	50	Discharge in LPM	*	*	700	680	655	640	610	590	570	545	520	490	460	430	400	365	330	260
2	MRF 22	7.5/5.5	65		*	*	*	*	*	*	*	*	820	790	760	720	700	650	600	560	510	450

* Denotes Overloading Region